















NEW

*Direct drains
with surface treatment*

DIRECT FLOOR DRAIN D110 AND 4" WITH PLASTIC/STAINLESS STEEL FRAME WITH NEPTUNE FLOAT

If the water level drops, the NEPTUNE float will close the outlet to prevent the back flow of odour from the sewage line. Made of PP, PS and stainless steel DIN 1.4301. Load capacity K3 (300 kg). Temperature resistance up to 70 °C. Tested in compliance with EN 1253.















💧 Flow rate (NEPTUNE float): 65 l/min

		PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	OUTLET DIAMETER	STAINLESS STEEL FRAME
		L1 394 X	9/486	0,36	110 mm	-
		L1 PVP 110 X				
		L1 394 N X	9/486	0,37	110 mm	✓
		L1 PVP 110 N X				
		L1 396 X	9/486	0,37	4"	-
		L1 PVP 4" X				
		L1 396 N X	9/486	0,38	4"	✓
		L1 PVP 4" N X				
		F1 394 X	9/486	0,36	110 mm	-
		F1 PVP 110 X				
		F1 394 N X	9/486	0,37	110 mm	✓
		F1 PVP 110 N X				
		F1 396 X	9/486	0,37	4"	-
		F1 PVP 4" X				
		F1 396 N X	9/486	0,38	4"	✓
		F1 PVP 4" N X				
		G1 394 X	9/486	0,36	110 mm	-
		G1 PVP 110 X				
		G1 394 N X	9/486	0,37	110 mm	✓
		G1 PVP 110 N X				
		G1 396 X	9/486	0,37	4"	-
		G1 PVP 4" X				
		G1 396 N X	9/486	0,38	4"	✓
		G1 PVP 4" N X				
		394 X	9/486	0,35	110 mm	-
		PVP 110 X				
		394 N X	9/486	0,36	110 mm	✓
		PVP 110 N X				
		396 X	9/486	0,36	4"	-
		PVP 4" X				
		396 N X	9/486	0,37	4"	✓
		PVP 4" N X				
		C 394 X	9/486	0,37	110 mm	✓
		C PVP 110 X				
		C 396 X	9/486	0,38	4"	✓
		C PVP 4" X				
		S 394 X	9/486	0,49	110 mm	✓
		S PVP 110 X				
		S 396 X	9/486	0,50	4"	✓
		S PVP 4" X				
		C1 394 X	8/384	0,51	110 mm	✓
		C1 PVP 110 X				
		C1 396 X	8/384	0,52	4"	✓
		C1 PVP 4" X				
		S1 394 X	8/384	0,67	110 mm	✓
		S1 PVP 110 X				
		S1 396 X	8/384	0,68	4"	✓
		S1 PVP 4" X				

DIRECT FLOOR DRAIN D110 AND 4" WITH PLASTIC/STAINLESS STEEL FRAME

Two options - plastic or stainless steel frame.
Made of PP and stainless steel DIN 1.4301.
Load capacity K3-300 kg. Temperature resistance up to 90 °C,
tested in compliance with EN 1253.













💧 Flow rate (water level): 40 l/min

		PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	OUTLET DIAMETER	STAINLESS STEEL FRAME
		L1 394	9/486	0,36	110 mm	-
		L1 PVP 110				
		L1 394 N	9/486	0,37	110 mm	✓
		L1 PVP 110 N				
		L1 396	9/486	0,37	4"	-
		L1 PVP 4"				
		L1 396 N	9/486	0,38	4"	✓
		L1 PVP 4" N				
		F1 394	9/486	0,36	110 mm	-
		F1 PVP 110				
		F1 394 N	9/486	0,37	110 mm	✓
		F1 PVP 110 N				
		F1 396	9/486	0,37	4"	-
		F1 PVP 4"				
		F1 396 N	9/486	0,38	4"	✓
		F1 PVP 4" N				
		G1 394	9/486	0,36	110 mm	-
		G1 PVP 110				
		G1 394 N	9/486	0,37	110 mm	✓
		G1 PVP 110 N				
		G1 396	9/486	0,37	4"	-
		G1 PVP 4"				
		G1 396 N	9/486	0,38	4"	✓
		G1 PVP 4" N				
		394	9/486	0,35	110 mm	-
		PVP 110				
		394 N	9/486	0,36	110 mm	✓
		PVP 110 N				
		396	9/486	0,36	4"	-
		PVP 4"				
		396 N	9/486	0,37	4"	✓
		PVP 4" N				
		C 394	9/486	0,37	110 mm	✓
		C PVP 110				
		C 396	9/486	0,38	4"	✓
		C PVP 4"				
		S 394	9/486	0,49	110 mm	✓
		S PVP 110				
		S 396	9/486	0,50	4"	✓
		S PVP 4"				
		C1 394	8/384	0,51	110 mm	✓
		C1 PVP 110				
		C1 396	8/384	0,52	4"	✓
		C1 PVP 4"				
		S1 394	8/384	0,67	110 mm	✓
		S1 PVP 110				
		S1 396	8/384	0,68	4"	✓
		S1 PVP 4"				

DIRECT FLOOR DRAIN D50 AND 2" WITH PLASTIC/STAINLESS STEEL FRAME

Two options - plastic or stainless steel frame.
 Made of PP and stainless steel DIN 1.4301.
 Load capacity K3-300 kg. Temperature resistance up to 90 °C,
 tested in compliance with EN 1253.

💧 **Flow rate (water level):** 50 l/min

		PART NUMBER NAME	PACKAGING [pcs/pallet]	WEIGHT [kg/pcs]	OUTLET DIAMETER	STAINLESS STEEL FRAME	
		L1 397 L1 PVP 50	9/486	0,33	50 mm	-	
		L1 397 N L1 PVP 50 N	9/486	0,35	50 mm	✓	
		L1 398 L1 PVP 2"	9/486	0,34	2"	-	
		L1 398 N L1 PVP 2" N	9/486	0,36	2"	✓	
		F1 397 F1 PVP 50	9/486	0,33	50 mm	-	
		F1 397 N F1 PVP 50 N	9/486	0,35	50 mm	✓	
		F1 398 F1 PVP 2"	9/486	0,34	2"	-	
		F1 398 N F1 PVP 2" N	9/486	0,36	2"	✓	
		G1 397 G1 PVP 50	9/486	0,33	50 mm	-	
		G1 397 N G1 PVP 50 N	9/486	0,35	50 mm	✓	
		G1 398 G1 PVP 2"	9/486	0,34	2"	-	
		G1 398 N G1 PVP 2" N	9/486	0,36	2"	✓	
		397 PVP 50	9/486	0,32	50 mm	-	
		397 N PVP 50 N	9/486	0,34	50 mm	✓	
		398 PVP 2"	9/486	0,33	2"	-	
		398 N PVP 2" N	9/486	0,35	2"	✓	
Type C	Type S		C 397 C PVP 50	9/486	0,34	50 mm	✓
			C 398 C PVP 2"	9/486	0,35	2"	✓
			S 397 S PVP 50	9/486	0,46	50 mm	✓
			S 398 S PVP 2"	9/486	0,47	2"	✓
Type C1	Type S1		C1 397 C1 PVP 50	8/384	0,48	50 mm	✓
			C1 398 C1 PVP 2"	8/384	0,49	2"	✓
			S1 397 S1 PVP 50	8/384	0,64	50 mm	✓
			S1 398 S1 PVP 2"	8/384	0,65	2"	✓